

A must-have for all professional chefs with big plans for sous vide cooking. Recommended for caterers, public caterers, and butchers.

Diamond XL is delivered fully assembled on a robust stainless steel bridge with an insulated bath tank (for 58-liter filling volume), stainless steel bath lid, and drain tap. This system is highly stable and robust with handles for easy transport.

Diamond has all of the features that make *Pearl* so special plus additional innovative functions like pre-programmed memory keys for meat, fish, and vegetables, straightforward HACCP data logging, and calibration functions.

When used in conjunction with the core temperature sensor, *Diamond* emits an alarm to indicate that your selected core temperature has been reached. The Easy **fusionchef** software gives you the ability to control, visualize, and log HACCP-relevant data for up to 24 *Diamond* units simultaneously.

The timers can be started separately from each other so you always stay in control, even during hectic situations. The timer that will expire next is shown continuously. A visual and acoustic signal informs the chef when the desired time has passed. The timer then goes into the minus range so you always know the total time that the food has been cooking.

Each of the pre-programmed memory keys (fish, meat, and vegetables) is set by default to five practical temperature values. Of course, you can edit these values at any time. It doesn't get any easier than that!

Diamond has extensive functionality that makes it an excellent addition to any professional kitchen.

As a closed unit, it greatly reduces evaporation of water, especially when cooking for long periods. As a result, safety shutdowns caused by a low water level are effectively avoided. When it's time for cleanup, simply put the water bath and bath lid into a dishwasher.

We recommend cooking no more than half of the bath volume of food(s) in kg. This is necessary to facilitate sufficient water circulation to guarantee a consistent temperature inside the bath.

XL bath (58 liters): up to about 27 kg



At a glance

- Temperature stability of ± 0.01 °C
- Splash-proof operating keypad
- Bright VFD temperature display
- Hygienic anti-fingerprint stainless hood
- Low-level water alarm
- Three timers
- Pre-programmed temperature memory keys (fish, meat, vegetables)
- Core temperature alarm (acoustic and visual)
- Straightforward HACCP-compliant data storage
- Guided-user auto calibration
- Simultaneous display of target and actual temperatures, core temperature and timer
- PC control and recording
- High-capacity pump (14l/min)
- Stainless steel protection grid (included)
- Vapor barrier protection
- Stainless steel bridge
- Insulated bath tank
- Bath lid constructed of stainless steel
- Drain tap
- Robust handles
- Protection class IPX4: Protection against spray water from all directions

Technical data

Designation	Diamond XL
Order number	9FT2B58
Temperature range	20.00 °C to 95.00 °C
Temperature stability	±0.01 °C
Temperature setting	Folientastatur
Temperature display	VFD-Display
Computer interface	RS232
Core temperature sensor	Pt100
Mains connection	230 V / 50-60 Hz
Current consumption	9.2 A
Heating capacity	2.0 kW
Flow rate at 0 bar	14 l/m
Pressure at 0 liter	0.3 bar
Voltage options	115 V / 60 Hz 230 V / 50-60 Hz
External dimensions (WxDxH)	537 x 697 x 424 mm
Weight	22.5 kg
Standards	CE RoHs
Low-level protection	Schwimmerschalter
Alarm notification	Akustisch Optisch
Permissible ambient temperature	5.00 °C to 40.00 °C

