

Product data sheet

Pearl S



Product Features

- ✓ Low-level water alarm
- ✓ Stainless steel protection grid (included)
- ✓ Hygienic anti-fingerprint stainless hood
- ✓ Splash-proof operating keypad
- ✓ Standards: CE, RoHS, WEEE
- ✓ High-capacity pump (14l/min)
- ✓ Temperature display in °C and °F



Performance values

230V/50Hz (Schuko Plug - CEE 7/4 Plug Type F)	
Heating capacity kW	2
Pump capacity flow pressure I/min	14
Pump capacity pressure bar	0.3
Power consumption A	9.2


Technical data

Available voltage versions	
Order No.	9FT1B20
Available voltage versions:	
9FT1B20.33	230V 50/60Hz (Schuko Plug - CEE 7/4 Plug Type F)

Bath	
Bath tank	Stainless steel
Bath cover	integrated

Electronics	
Temperature display	LED





Temperature values	
Working temperature range °C	+20 +95
Temperature stability °C	±0.03
Ambient temperature °C	+5 +40

Other	
IP Code	IP X4

Refer to www.fusionchef.de for more information regarding the entire Fusionchef product portfolio. Technical changes without prior notification. Images may deviate from the original. | Datasheet No.EN9FT1B20/250729