

Product data sheet

Pearl L



Product Features

- ✓ Low-level water alarm
- ✓ Stainless steel protection grid (included)
- ✓ Hygienic anti-fingerprint stainless hood
- ✓ Splash-proof operating keypad
- ✓ Standards: CE, RoHS, WEEE
- ✓ High-capacity pump (14l/min)
- ✓ Temperature display in °C and °F

Performance values

230V/50Hz (Schuko Plug - CEE 7/4 Plug Type F)

Heating capacity kW 2

Pump capacity flow pressure l/min 14

Pump capacity pressure bar 0.3

Power consumption A 9.2

Technical data

Available voltage versions

Order No. 9FT1B44

Available voltage versions:

9FT1B44.33 230V 50/60Hz (Schuko Plug - CEE 7/4 Plug Type F)

Bath

Bath tank Stainless steel

Bath cover integrated

Electronics

Temperature display LED

Dimensions and volumes

Weight kg	21
Total dimensions cm (W × L × H)	53.7 x 69.7 x 37.4
Filling volume l	44

Temperature values

Working temperature range °C	+20 ... +95
Temperature stability °C	±0.03
Ambient temperature °C	+5 ... +40

Other

IP Code	IP X4
---------	-------

Refer to www.fusionchef.de for more information regarding the entire Fusionchef product portfolio. Technical changes without prior notification. Images may deviate from the original. | Datasheet No.EN9FT1B44/250729