

Product data sheet

Diamond XL



Product Features

- ✓ 3 Timer
- ✓ Guided-user auto calibration
- ✓ Stainless steel protection grid (included)
- ✓ Straightforward HACCP-compliant data storage
- ✓ Simultaneous display of target and actual temperatures, core temperature and timer
- ✓ Hygienic anti-fingerprint stainless hood
- ✓ Core temperature alarm (acoustic and visual)
- ✓ Bright VFD temperature display

Performance values

230V/50Hz (Schuko Plug - CEE 7/4 Plug Type F)

Heating capacity kW	2
Pump capacity flow pressure l/min	14
Pump capacity pressure bar	0.3
Power consumption A	9.2

Technical data

Available voltage versions

Order No. 9FT2B58

Available voltage versions:

9FT2B58.33 230V 50/60Hz (Schuko Plug - CEE 7/4 Plug Type F)

Bath

Bath tank	Stainless steel
Bath cover	integrated

Electronics

Interfaces	RS232
External pt100 sensor connection	integrated
Temperature display	VFD

Dimensions and volumes

Weight kg	22.5
Total dimensions cm (W × L × H)	53.7 x 69.7 x 42.4
Filling volume l	58

Temperature values

Working temperature range °C	+20 ... +95
Temperature stability °C	±0.01
Ambient temperature °C	+5 ... +40

Other

IP Code	IP X4
---------	-------

Refer to www.fusionchef.de for more information regarding the entire Fusionchef product portfolio. Technical changes without prior notification. Images may deviate from the original. | Datasheet No.EN9FT2B58/250729